

# TECHNICAL DATA SHEET



## Anglesey basin tap 5"

- [T6] Basin Pillar Taps 5
- [T2] Anglesey tap handles (pair)

### Product Specification

<b>Finishes</b>	Chrome plated
<b>Product Type</b>	Traditional
<b>Material</b>	Bodies are of all brass construction

### Additional Information

Supplied with flow straightener - this is for use with low water pressure  
 Supplied with aerator - this is for use with high water pressure

System Pressure	.2 bar	.5 bar	1.0 bar	2.0 bar	3.0 bar
with flow straightener*	12.70	13.80	17.60	22.20	22.60
with aerator*	4.80	7.90	9.10	10.50	11.60

\* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap

### Guarantee



See our website for terms and conditions

### Compliance / Approvals

**BS 5412:1996**  
 Specification for low-resistance single taps and combination tap assemblies (nominal size 1/2" and 3/4") suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)

**BS EN 200:2008**  
 Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification

