

TECHNICAL DATA SHEET



Anglesey 3 tap hole basin mixer with pop up waste

- [T14] Three Tap Hole tap, with pop up (excluding tap heads & base)
- [T2] Anglesey tap handles (pair)

Product Specification

| | |
|---------------------|--------------------------------------|
| Finishes | Chrome plated |
| Product Type | Traditional |
| Material | Bodies are of all brass construction |

Additional Information

Supplied with flow straightener - this is for use with low water pressure
 Supplied with aerator - this is for use with high water pressure

| System Pressure | .2 bar | .5 bar | 1.0 bar | 2.0 bar | 3.0 bar |
|-------------------------|--------|--------|---------|---------|---------|
| with flow straightener* | 9.50 | 15.80 | 17.20 | 19.30 | 21.20 |
| with aerator* | 4.10 | 7.70 | 8.90 | 10.60 | 11.60 |

* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap

Guarantee



See our website for terms and conditions

Compliance / Approvals

BS 5412:1996
 Specification for low-resistance single taps and combination tap assemblies (nominal size ? and ?) suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)

BS EN 200:2008
 Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification

