

# TECHNICAL DATA SHEET



## Anglesey Angled Bath Shower Mixer - Wall mounted

- [T9] Angled Bath Shower Mixer (Including the standard cradle, 'S' adjuster, Claremont, Anglesey & Birkenhead divertor handle, hose, ceramic telephone handset, excluding tap heads, base and unions)
- [T17-2] Wall mounting unions (for Bath Shower Mixer & Bath Filler, 3/4
- [T2] Anglesey tap handles (pair)

### Product Specification

<b>Finishes</b>	Chrome plated
<b>Product Type</b>	Traditional
<b>Material</b>	Bodies are of all brass construction

### Additional Information

Supplied with flow straightener - this is for use with low water pressure  
 Supplied with aerator - this is for use with high water pressure

<b>System Pressure</b>	.2 bar	.5 bar	1.0 bar	2.0 bar	3.0 bar
<b>with flow straightener*</b>	22.00	22.60	25.20	27.20	29.00
<b>with aerator*</b>	5.60	10.70	11.60	14.30	15.60

\* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap

### Guarantee



See our website for terms and conditions

### Compliance / Approvals

**BS 5412:1996**

Specification for low-resistance single taps and combination tap assemblies (nominal size ? and ?) suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)

**BS EN 200:2008**

Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification

