

TECHNICAL DATA SHEET

Burlington[®]
Yesterday's designs TODAY'S TECHNOLOGY

Anglesey Regent bath tap

- [T7] Bath Pillar Taps(excluding tap heads & base)
- [T2] Anglesey tap handles (pair)
- [T4A] Regent large pair of tap bases (for Bath taps, Bath shower mixers & Bath fillers - pair)

Product Specification

Finishes Chrome plated
Product Type Traditional
Material Bodies are of all brass construction

Additional Information

Supplied with flow straightener - this is for use with low water pressure
 Supplied with aerator - this is for use with high water pressure

| System Pressure | .2 bar | .5 bar | 1.0 bar | 2.0 bar | 3.0 bar |
|-------------------------|--------|--------|---------|---------|---------|
| with flow straightener* | 14.20 | 16.50 | 19.50 | 23.10 | 23.70 |
| with aerator* | 4.80 | 7.90 | 9.10 | 10.50 | 11.60 |

* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap

Guarantee



See our website for terms and conditions

Compliance / Approvals

BS 5412:1996
 Specification for low-resistance single taps and combination tap assemblies (nominal size ? and ?) suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)
BS EN 200:2008
 Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification

