

TECHNICAL DATA SHEET

Burlington[®]
Yesterday's designs TODAY'S TECHNOLOGY

Anglesey Regent bidet mixer with high / low central Burlington ceramic indice with pop-up waste

- [T15] Bidet Mixer, with pop up (excluding tap heads & base)
- [T2] Anglesey tap handles (pair)
- [T4B] Regent small single tap base (for Basin & Bidet monoblocs - single)

Product Specification

Finishes	Chrome plated
Product Type	Traditional
Material	Bodies are of all brass construction

Additional Information

Supplied with flow straightener - this is for use with low water pressure
 Supplied with aerator - this is for use with high water pressure

System Pressure	.2 bar	.5 bar	1.0 bar	2.0 bar	3.0 bar
with flow straightener*	10.30	15.20	16.90	19.40	20.70
with aerator*	3.80	5.30	7.30	8.30	10.50

* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap



Guarantee



See our website for terms and conditions

Compliance / Approvals

BS 5412:1996
 Specification for low-resistance single taps and combination tap assemblies (nominal size 1/2" and 3/4") suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)

BS EN 200:2008
 Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification

