

TECHNICAL DATA SHEET



Birkenhead Angled Bath Filler - wall mounted

- [T11] Angled Bath Filler (excluding tap heads, bases and unions)
- [T17-2] Wall mounting unions (for Bath Shower Mixer & Bath Filler, 3/4)
- [T3] Birkenhead tap handle (pair)

Product Specification

Finishes	Chrome plated
Product Type	Traditional
Material	Bodies are of all brass construction

Additional Information

Supplied with flow straightener - this is for use with low water pressure
 Supplied with aerator - this is for use with high water pressure

System Pressure	.2 bar	.5 bar	1.0 bar	2.0 bar	3.0 bar
with flow straightener*	21.00	21.70	24.20	26.50	28.00
with aerator*	5.40	10.30	11.50	13.60	15.50

* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap



Guarantee



See our website for terms and conditions

Compliance / Approvals

BS 5412:1996
 Specification for low-resistance single taps and combination tap assemblies (nominal size ? and ?) suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)

BS EN 200:2008
 Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification

