

# TECHNICAL DATA SHEET

## Birkenhead Wall mounted Bath Shower Mixer with rigid riser, straight arm & 6" rose

- [T8] Bath Shower Mixer (Including the standard cradle, 'S' adjuster, ceramic diverter, hose, ceramic telephone handset, excluding tap heads, bases and unions)
- [T17-2] Wall mounting unions (for Bath Shower Mixer & Bath Filler, 3/4
- [V22] Extended vertical riser (with two adjustable vertical riser wall brackets)
- [V11-1] Straight shower arm for vertical riser mounting
- [V16] 6 Shower Rose
- [T3] Birkenhead tap handle (pair)

### Product Specification

|                     |                                      |
|---------------------|--------------------------------------|
| <b>Finishes</b>     | Chrome plated                        |
| <b>Product Type</b> | Traditional                          |
| <b>Material</b>     | Bodies are of all brass construction |

### Additional Information

Supplied with flow straightener - this is for use with low water pressure  
 Supplied with aerator - this is for use with high water pressure

|                                |        |        |         |         |         |
|--------------------------------|--------|--------|---------|---------|---------|
| <b>System Pressure</b>         | .2 bar | .5 bar | 1.0 bar | 2.0 bar | 3.0 bar |
| <b>with flow straightener*</b> | 22.00  | 22.60  | 25.20   | 27.20   | 29.00   |
| <b>with aerator*</b>           | 5.60   | 10.50  | 11.70   | 14.10   | 15.50   |

\* The tap comes with a factory-fitted flow straightener for low pressure water systems. If the water flow is high, replace the factory-fitted flow straightener with the high pressure aerator. Both the aerator and a Neoperl key to replace the flow straightener are supplied with every tap

|                        |        |        |         |         |         |
|------------------------|--------|--------|---------|---------|---------|
| <b>System Pressure</b> | .2 bar | .5 bar | 1.0 bar | 2.0 bar | 3.0 bar |
| <b>Shower Rose</b>     | 6.90   | 11.50  | 12.30   | 14.10   | 16.20   |

### Guarantee



See our website for terms and conditions

### Compliance / Approvals

#### BS 5412:1996

Specification for low-resistance single taps and combination tap assemblies (nominal size ? and ?) suitable for operation at PN 10 max. and a minimum flow pressure of 0.01 MPa (0.1 bar)

#### BS EN 200:2008

Sanitary tapware. Single taps and combination taps for water supply systems of type 1 and type 2. General technical specification



